

# PERFORMANCE TUNE-UP

## PARK RE-OPENING CHECKLIST

### INSPECT

1



REMOVE

Ensure any large debris that may have fallen on the ride length is removed. Pay particular attention to any water injection or removal points.

☐

2



TAKE STOCK

Review the inventory to ensure sufficient spare parts and ride vehicle quantities.

☐

3



INSPECT

Check the fiberglass (interior and exterior) as well as steel components for any signs of damage or corrosion. Check the fiberglass joints for gaps, misalignment and/or degraded sealant.

☐

4



REPORT

Identify any structural problems to the proper authority and do not use the deficient flume until the problem(s) have been corrected.

☐

### CONDUCT

1



REPAIR

Identify & fix any gelcoat chips or cracks as well as missing/deteriorated sealant.

☐

2



WASH & WAX

Clean the ride surface. The exterior can be cleaned with a pressure washer at a pressure not exceeding 2000 psi.

☐

3



PERFORM

Conduct any maintenance or start-up procedures on pumps, scales, conveyors, lighting systems etc.

☐

4



TURN ON

Initiate water and check for visible dry spots due to blocked sprinklers.

☐

### VALIDATE

1



CONFIRM

Double check that flow rates and water levels are correct.

☐

2



RIDE

Test the ride with a lifeguard or water ride attendant before opening to public.

☐